

Windows®. Life without Walls™.
Fujitsu recommends Windows 7.

Data Sheet

Fujitsu ESPRIMO C700

Desktop PC

The ultra small professional PC

Take advantage of the newly designed ESPRIMO C700, the compact ultra small form factor PC with maximum performance, in office environments with limited space. Comfortable working - ergonomic, quiet and reliable. The ESPRIMO C700 with its intelligent design offers easy and reliable administration and with a PCIe x16 slot is simple to expand. Equipped with an up to 90% energy efficient integrated power supply unit and selected materials this ultra small form factor PC with a volume of 7.4 liters meets numerous environmental standards, such as ENERGY STAR®.



Compact design

Top quality PC for office environments with little space; can be positioned both horizontally and vertically.

- Ultra small form factor PC with only 7.4 liters volume, integrated, highly efficient power supply, legacy interfaces and powered serial ports

Highest energy efficiency coupled with intelligent performance

Low power consumption combined with top performance

- State-of-the-art Intel® Core™ processors with Turbo Boost und Hyper-Threading technology and an up to 90% energy efficient power supply and ENERGY STAR® certification

Compact but expandable

Smallest ESPRIMO PC system with discrete graphics card, multi-monitor solutions are possible

- Up to a 500GB disk and PCIe x16 slot



Family concept

Reduced test and evaluation costs for the existing PC infrastructure.

- Uniform technology platform and bit image for the 700 series from Fujitsu



Components

Processor	Intel® Core™ i7-2600 processor (4 Cores / 8 Threads, 3.40 GHz, 8 MB, Intel® HD Graphics 2000) Intel® Core™ i5-2500 processor (4 Cores / 4 Threads, 3.30 GHz, 6 MB, Intel® HD Graphics 2000) Intel® Core™ i5-2400 processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® HD Graphics 2000) Intel® Core™ i3-2100 processor (2 Cores / 4 Threads, 3.10 GHz, 3 MB, Intel® HD Graphics 2000) Intel® Pentium® processor G840 (2 Cores / 2 Threads, 2.80 GHz, 3 MB, Intel® HD Graphics) Intel® Pentium® processor G620 (2 Cores / 2 Threads, 2.60 GHz, 3 MB, Intel® HD Graphics)
Operating system	Genuine Windows® 7 Home Basic (EM) 32-bit Genuine Windows® 7 Home Premium 64-bit Genuine Windows® 7 Professional 32-bit Genuine Windows® 7 Professional 64-bit
Operating system compatible	openSUSE Linux Genuine Windows Vista® Genuine Windows® XP
Operating system notes	Buy Microsoft® Office 2010 to use the full-featured Office software on this PC. Limited Windows XP support. Microsoft discontinued Windows XP certification on system level.
Memory modules	2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM 4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1333 MHz, PC3-10600, DIMM
Hard disk drives (internal)	SSD SATA, 128 GB, 2.5-inch SATA III, 7200 rpm, 1000 GB, 3.5-inch SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical SATA III, 7200 rpm, 500 GB, 3.5-inch SATA III, 7200 rpm, 320 GB, 3.5-inch
Hard disk notes	Up to 18 GB of HDD space is reserved for system recovery
Graphics add on cards (optional)	NVIDIA® Quadro® NVS 300 LP, 512 MB NVIDIA® GeForce® 405 display port low profile, 512 MB LFH59/ 2x DVI-I adapter cable LFH59/ 2x DP adapter cable DP to DVI-D (single link) Adapter Cable
Drives (optional)	DVD Super Multi DVD Super Multi Slot-in slim
Interface add on cards/components (optional)	WLAN III, 802.11g/Draft-n (Windows only) USB 3.0 PCIe x1 Parallel Interface eSATA Interface Dual serial card PCIe x1, powered Dual serial card PCIe x1
Base unit	ESPRIMO C700
Mainboard	
Mainboard type	D3064
Formfactor	proprietary
Chipset	Intel® Q65
Processor socket	LGA 1155

Mainboard

Processor quantity maximum	1
Memory slots	4 DIMM (DDR3)
Supported capacity RAM (max.)	32 GB
Memory frequency	1333 MHz
Memory notes	Dual channel support. For dual channel performance, identical memory modules in each channel are necessary (minimum 2 modules). > 16 GB support with future memory modules
LAN	10/100/1000 MBit/s Intel® 82579 V
BIOS version	AMI Aptio 4.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio

I/O controller on board

Serial ATA total	3
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI

Interfaces

Audio: line-in	1
Audio: line-out	1
Front audio: microphone	1
Front audio: headphone	1
USB 2.0 total	12
USB 3.0 total	optional
USB front	4
USB rear	6
USB internal	2
VGA	1 (via DVI to VGA adapter, part of shipment)
DisplayPort	1
DVI	1 (DVI-I)
Serial (RS-232)	2 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1 (optional) (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Input device / components

	Optical USB tilt wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO

Drive bays

Drive bays total	2
3.5-inch internal bays	1
5.25-inch external bays	1
Drive bay notes	slim optical disc drive

Slots

PCI-Express 2.0 x16	1 x (220 mm) Low profile
---------------------	--------------------------

Graphics on board

Graphics brand name	Intel® HD Graphics or HD Graphics 2000 (depending on CPU)
Shared video memory	up to 1759 MB
TFT resolution (VGA)	1024 x 768 pixel 1280 x 1024 pixel 1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1600 x 1200 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel 1440 x 900 pixel 1600 x 900 pixel 1680 x 1050 pixel 1920 x 1080 pixel 1920 x 1200 pixel 2560 x 1440 pixel 2560 x 1600 pixel
Graphics features	Dual display support DirectX 10.1 HDCP support OpenGL® 2.1 For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)
Graphics notes	Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 87% / 90% / 87%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	225 W
Power factor correction/active power	active
Monitor outlet	No

Power consumption

Power consumption note	See white paper Energy Consumption
-------------------------------	------------------------------------

Heat dissipation

Heat dissipation notes	See white paper Energy Consumption
-------------------------------	------------------------------------

Noise for standard configuration (HDD, ODD)

Noise emission	According to ISO9296
Related Processors for noise	Core i3-2100 ; Core i5-2400
Noise Operation mode 1: ODD load (Blue angel requirement)	4.6 B / 32.0 dB(A)
Noise Operation mode 2: HDD load (Blue angel requirement)	3.6 B / 22.1 dB(A)

Noise for standard configuration (HDD, ODD)

Noise Operation mode 3: CPU 90% load (Blue angel requirement) 3.6 B / 22 dB(A) ; 3.9 B / 25.3 dB(A)

Noise Operation mode 4: High load 3.7 B / 22 dB(A) ; 4.0 B / 25.2 dB(A)

Idle mode (Blue Angel requirement) 3.6 B / 22 dB(A)

Noise notes / description A weighted sound power level L_{wad} (in B) / workplace related A-weighted sound pressure level L_{pAm} (in dB(A)), Bystander position

Dimensions / Weight / Environmental

Dimensions (W x D x H) 265 x 315 x 88 mm

Operating position Vertical / horizontal (no feet needed)

Weight approx. 9 kg

Weight notes Actual weight may vary depending on configuration

Operating ambient temperature 10 - 35C

Compliance

Product ESPRIMO C700

Germany Blauer Engel / Blue Angel in progress

Europe CE
Nordic Swan in progress

USA/Canada FCC Class B
CSA

Global RoHS (Restriction of hazardous substances)
WEEE (Waste electrical and electronical equipment)
Microsoft Operating Systems (HCT / HCL entry / WHQL)
ENERGY STAR®
EPEAT® in progress (dedicated regions)

Compliance link <https://sp.ts.fujitsu.com/sites/certificates/default.aspx>

Additional Software

Additional software (preinstalled) Nero Essentials S (burning software)
Fujitsu Recovery (Hard Disk Based Recovery)

Additional software (optional) Recovery DVD for Windows®
Drivers & Utilities DVD (DUDVD)
Nero 9 Essentials XL

Miscellaneous

Keyboard on (Special Fujitsu keyboard required)
Thermal management
Extended lifetime

Compatibility (references)

DMI 2.0
PC 2001
WMI 1.5
USB 2.0
SMBIOS

Manageability

Manageability technology DeskUpdate Driver management
PXE 2.1 Boot code
Wake up from S5 (off mode)
Intrusion switch (optional)
Intel® Standard Manageability

Manageability software DeskView 10.x client management including:

Manageability

DeskView components	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Advanced alerts (ASF implementation) Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability http://www.altiris.com/fujitsu

Security

System protection	Kensington Lock support Eye for padlock Optional: Integrated cabinet lock
Audit proof protection	Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
Access protection	User and supervisor BIOS password Hard disk password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader

Serviceability

EasyFix
EasyChange for HDD

Packaging information

Packaging dimension	467x265x540 mm
Max. quantity / pallet	28
Material - Weight (g) Carton	940 g
Material - Weight (g) EPS / PS	190 g
Material - Weight (g) PE	appr. 60 g
Packaging notes	printed user documentation is bleached in chlorine free process

Warranty

Standard Warranty	1 year
Service level	Bring-In / On-Site Service (depending on country)

Maintenance and Support Services - the perfect extension

Recommended Service	5x9, Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://ts.fujitsu.com/Supportservice

More information

Fujitsu platform solutions

In addition to Fujitsu ESPRIMO C700, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure-as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu ESPRIMO C700, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://ts.fujitsu.com/esprimo>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

CONTACT

FUJITSU Technology Solutions
Website: <http://ts.fujitsu.com>
2011-06-01 CE-EN

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright Fujitsu Technology Solutions